



## MetSens600

Compact Weather Sensor for Temperature, RH, Barometric Pressure, Wind, and Rainfall Indication with Compass

**IEI**  
Sales & Support  
(435) 755-0774  
www.inmtn.com



# Measures 6 Common Meteorological Parameters

IEC 61724-1 Compliant

### Overview

The MetSens600 compact weather sensor measures wind speed and direction via an ultrasonic sensor, as well as air temperature, relative humidity, and barometric pressure, in a single, combined instrument mounted inside three double-louvered, naturally aspirated radiation shields with no moving parts. An optical precipitation sensing element senses fine amounts of water. An integrated electronic compass allows the MetSens600 to provide accurate, relative wind direction measurements without being oriented in a particular way,

making installation easier. WMO average wind speed and direction and gust, temperature, relative humidity, barometric pressure, absolute humidity, air density, wet bulb temperature, rainfall total, and rainfall intensity data are provided. The MetSens600 is compatible and easily integrated with the [MeteoPV Solar Resource Platform](#) and any Campbell Scientific data logger using SDI-12, RS-485, ModbusRS-485, or NMEA RS-232.

### Benefits and Features

- › Quality measurements
- › Fast and simple to install
- › Compact, integrated design
- › Lightweight and robust

### Specifications

Measurements Made	Air temperature, barometric pressure, precipitation, relative humidity, wind direction, and wind speed.	› Where applicable, all individual parameters meet or exceed specifications of IEC 61724-1 (2017, 2021).	
Sampling Rate	1 Hz	Operating Temperature Range	-40° to +70°C
Digital Communication Modes	Serial RS-232, RS-485, SDI-12, NMEA, Modbus, ASCII	Operating Voltage	5 to 30 Vdc
IP Rating	66	Typical Current Drain @ 12 Vdc	› 0.7 mA (eco-power mode; 1 hour polled) › 25 mA (continuous high mode)
Compliance	› CE, RoHS		

Weight 0.8 kg (1.8 lb)

### Air Temperature Measurement

Measurement Range -40° to +70°C

Resolution 0.1°C

Accuracy ±0.3°C (@ 20°C)

### Relative Humidity Measurement

Measurement Range 0 to 100%

Resolution 0.1

Accuracy ±2% @ 20°C (10 to 90% RH)

### Barometric Pressure Measurement

Measurement Range 300 to 1100 hPa

Resolution 0.1 hPa

Accuracy ±0.5 hPa (@ 25°C)

### Wind Speed Measurement

Measurement Range 0.01 to 60 m s<sup>-1</sup>

Accuracy > ±3% (up to 40 m s<sup>-1</sup>)

> ±5% (up to 60 m s<sup>-1</sup>)

Resolution 0.01 m s<sup>-1</sup>

Starting Threshold 0.01 m s<sup>-1</sup>

### Wind Direction Measurement

Measurement Range 0° to 359°

Accuracy ±3° (up to 60 m s<sup>-1</sup>)

Resolution 1°

### Precipitation Measurement

Measurement Type Optical

Measurement Range 0 to > 300 mm h<sup>-1</sup>

Precipitation Resolution 0.08 mm

Repeatability 3%

### Compass

Measurement Range 0 to 359°

Resolution 1°

Units of Measure Degrees

Accuracy ±3°



Sales & Support:  
(435) 755-0774  
<http://www.inmtn.com>  
[info@inmtn.com](mailto:info@inmtn.com)



Campbell Scientific, Inc. | 815 W 1800 N | Logan, UT 84321-1784 | (435) 227-9120 | [www.campbellsci.com](http://www.campbellsci.com)  
AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | USA

© 2024 Campbell Scientific, Inc. | 01/26/2024